


VIDRIERA ARTE SAN SL

**FICHA TECNICA
DEL LUXMAT**

A CONTINUACION LE DETALLAMOS LA DOCUMENTACION SOBRE EL VIDRIO ACIDO LUXMAT:

1 FICHA TECNICA



PRODUCT SPECIFICATIONS

R&D and Technical department of SEVASA TECHNOLOGICS

CERTIFIES :

- ↳ The product **LUXMAT®** is produced by SEVASATECHNOLOGICS.
- ↳ The product **LUXMAT®** is produced on float glass following norm *UNE 572-1994* which is based on the document *ISO/TC 160 N56 Glass for construction*.
- ↳ The following values are based on internal measurements on **Guardian ExtraClear 4mm** substrate.

LUXMAT® 4 m m Extra Clear	Values
Transmittance (%)	$\tau \geq 91.5$
Haze (%)	8 ± 2
Clarity (%)	55 ± 5
Gloss (@60°)	60 ± 10
DOI	3 ± 1.5
RO	2 ± 1.5
Roughness (μm)	$R_a \leq 0,900$ $R_z \leq 2,200$

- ↳ Measures taken with BYK-Gardner and Rhopoint Instruments hardware.

TECH

Calanda, September 2019

SEVASATECHNOLOGICS quality department

SEVASA TECHNOLOGICS, S.A

Po. Ind. La Fuensalada – Parcela 4. E-44570 Calanda (Teruel - Spain)
 T: +34 978 110 061 - info@sevasatechnologies.com - www.sevasa.com